

STICK a TILE CRACK FILLER is a white cement-based general purpose crack filler which can be used on exterior or interior surfaces.

SURFACE PREPARATION

- Cracks should be opened sufficiently to ensure **STICK a TILE CRACK FILLER** can be applied correctly.
- Surface must be firm and free of dust, loose partials, mould, oil, grease, wax polish and organic growth.
- Can be used on concrete, masonry, stone, and cement renderings.
- Painted surfaces must be sanded lightly.
- Ensure all nails, screws, etc. are removed from cracks or holes that are been filled.

MIXING AND APPLICATION

- Gradually mix 3 parts **STICK a TILE CRACK FILLER** to 1 part of cold clean water.
- Mix to a lump free smooth, heavy paste in a clean container.
- Allow to stand for 5 minutes before using
- Use the product within 45 minutes of mixing.
- Apply into the cracks with a putty knife or trowel.
- Fill cracks slightly higher than the cracks, or holes, and smooth off with a putty knife or trowel within 20 minutes of application.
- Any cracks bigger than 10mm need to be applied in more than one application to avoid possible slumping.
- Leave to dry for 2 hours before sanding.
- Dry to touch within 45 minutes.
- Initial setting time is 2 hours in normal conditions, longer in colder weather.
- Final setting time is 12 hours in normal conditions, longer in colder weather.
- Painting is recommended after 6 hours with PVA Paints and 24 hours for solvent based paints.

Do not add too much water or attempt to extend the working time by adding more water as this will cause the filler to be weak with a tendency to crumble or slump.





PRODUCT PROPERTIES

Working Time:	45 minutes
Final Setting Time:	12 hours at 23°C
Recoating/ 2 nd Application:	2 hours at 23°C
Application Temperature:	Do not apply below 5°C or above 30°C
Shelf life:	6 Months from production
Storage:	Store product in a dry and covered area at temperatures between (10°C and 30°C). Do not store directly on floor surface. Avoid large changes in temperature and humidity in storage environment.

GUARANTEE

We guarantee that **STICK a TILE** products meet the required specifications and will be free of defect. Any guarantee regarding the performance of **STICK a TILE** product will be subject to the professional and practical application of **STICK a TILE** product in accordance with our instructions and specifications. The guarantee would become void should the **STICK a TILE** product be contaminated or altered by the addition of cement, sand or substance other than recommended by us.


We have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain professional advice from the **STICK a TILE** technical department.

NOTE: We required to be informed within a reasonable time of suspected defect/s and afforded the opportunity, and time, to investigate the problem in detail. **NO** remedial work is to commence until our final findings and assessments have been made in writing.

WARNING

Do not ingest. Keep away from children and pets. Do not empty in drains. Contact **STICK a TILE** for further Health and Safety Information.





PRECAUTIONS

In the event of eye contact, rinse thoroughly with cold clean water and seek medical assistance if irritation or discomfort should occur. If ingested consult a doctor immediately and drink lots of milk. Wear the appropriate safety equipment, rubber gloves, a mask and ensure the area where the product is been used is well ventilated.

IMPORTANT NOTICE

The information supplied by **STICK a TILE** on this data sheet is deemed correct and is supplied as a guideline only. **STICK a TILE** does not accept any liability for any injury, damage or loss resulting in the use of this product.

STICK a TILE reserves the right to change the information on this data sheet as and when deemed necessary.

For detailed specifications on the product usage contact **STICK a TILE** on:

Tel: (011) 626 1981

Email: info@stickatile.com

